

FORM PTO-1390  
(REV. 6-87)U.S. DEPARTMENT OF COMMERCE  
PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

1066-02

**TRANSMITTAL LETTER TO THE UNITED STATES  
DESIGNATED/ELECTED OFFICE (DO/EO/US)****10/088818**INTERNATIONAL APPLICATION NO.  
PCT/JP01/05369INTERNATIONAL FILING DATE  
30 SEPTEMBER 1999 (30.09.99)

PRIORITY DATE CLAIMED

TITLE OF INVENTION  
DROP-BOTTOM CONTAINERAPPLICANT(S) FOR DO/EO/US  
Ritsuo Nakajima

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items under 35 U.S.C. 371:

1. ☒ This express request to immediately begin national examination procedures (35 U.S.C. 371(f)).
2. ☒ The U.S. National Fee (35 U.S.C. 371(c)(1)) and other fees as follows:

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS	4 -20=	0	x \$18.00	\$
	INDEPENDENT CLAIMS	2 -3=	0	x \$84.00	
	MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$280.00	
	BASIC NATIONAL FEE (37 CFR 1.492(a)(1)-(4)):				
	<input type="checkbox"/> International preliminary examination fee paid to USPTO (37 CFR 1.482).....				\$710.00
	<input type="checkbox"/> No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)).....				\$740.00
	<input type="checkbox"/> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO.....				\$1,040.00
	<input type="checkbox"/> International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2) to (4).....				\$ 100.00
	<input checked="" type="checkbox"/> International Search Report enclosed .....				\$890.00
	Surcharge of \$ _____ for furnishing the National fee or oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 mos. from the earliest claimed priority date (37 CFR 1.482(e)).				\$130.00
	TOTAL OF ABOVE CALCULATIONS				\$890.00
	Reduction by 1/2 for filing by small entity, if applicable. Affidavits must be filed also. (Note 37 CFR 1.9, 1.27, 1.28.)				\$445.00
	SUBTOTAL				\$445.00
	Processing fee of \$ _____ for furnishing the English Translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 mos. from the earliest claimed priority date (37 CFR 1.482(f)).				\$130.00
	TOTAL NATIONAL FEE				\$445.00
	Fee for recording the enclosed assignment (37 CFR 1.21(h)).				\$40.00
	TOTAL FEES ENCLOSED				\$445.00

- a. ☒ A check in the amount of \$445.00 to cover the above fees is enclosed.
- b. ☐ Please charge my Deposit Account No. 13-3405 in the amount of \$ \_\_\_\_\_ to cover the above fees.  
A duplicate copy of this sheet is enclosed.
- c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 13-3405. A duplicate copy of this sheet is enclosed.

JC10 Rec'd PCT/PTO 22 MAR 2002

3. A copy of the International Application as filed (35 U.S.C. 371(c)(2))
- a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
  - b. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
  - c. ☒ has been transmitted by the International Bureau.
4. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
5. Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
- a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
  - b. ☐ have been transmitted by the International Bureau.
6. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
7. ☐ An oath or declaration of the inventor (35 U.S.C. 371(c)(4)).
8. ☐ A translation of the Annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Other document(s) or information included:

9. ☒ An Information Disclosure Statement under 37 C.F.R. 1.97 and 1.98.
10. ☐ An Assignment document for recording and a Recordation Form Cover Sheet - Patents Only. Please mail the recorded assignment document to the person whose signature, name and address appears at the bottom of this page.
11. The above checked items are being transmitted
- a. ☐ before the 18th month publication.
  - b. ☐ after publication and the Article 20 communication but before 20 months from the priority date.
  - c. ☐ after 20 months but before 22 months (surcharge and/or processing fee included).
  - d. ☐ after 22 months (surcharge and/or processing fee included).
- Note:** Petition to revive (37 C.F.R. 1.137(a) or (b)) is necessary if 35 U.S.C. 371 requirements submitted after 22 months and no proper demand for International Preliminary Examination was made by 19 months from the earliest claimed priority date.
- e. ☒ by 30 months and a proper demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
  - f. ☐ after 30 months but before 32 months and a proper demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date (surcharge and/or processing fee included).
  - g. ☐ after 32 months (surcharge and/or processing fee included).
- Note:** Petition to revive (37 C.F.R. 1.137(a) or (b)) is necessary if 35 U.S.C. 371 requirements submitted after 32 months and a proper demand for International Preliminary Examination was made by 19 months from the earliest claimed priority date.
12. At the time of transmittal, the time limit for amending claims under Article 19
- a. ☐ has expired and no amendments were made.
  - b. ☐ has not yet expired.
13. ☐ Certain requirements under 35 U.S.C. 371 were previously submitted by the applicant on \_\_\_\_\_, namely:

SCHNADER HARRISON SEGAL & LEWIS

Date: 22 MAR 2002

By: \_\_\_\_\_

T. Daniel Christenbury, Reg. No. 31,750  
1600 Market Street, 36<sup>th</sup> Floor  
Philadelphia, PA 19103

10088818 10/088818

1070 Rec'd PCT/PTO 22 MAR 2002

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE



22469

PATENT TRADEMARK OFFICE

Art Unit :  
Examiner :  
Serial No. :  
Filed : Herewith  
PCT No. : PCT/JP99/05369  
PCT Filed : September 30, 1999  
Inventors : Ritsuo Nakajima  
Title : DROP-BOTTOM C-1-ONTAINER

Docket: 1066-02

Conf. No.

Dated: March 22, 2002

**PRELIMINARY AMENDMENT**

**BOX PCT**

Commissioner for Patents  
Washington, DC 20231

Sir:

Prior to action on the merits of the case, kindly amend the above-identified application as follows:

**In the Claims** (Clean copy as amended)

3. (Amended) A bottom opening type container according to claim 1, wherein a returning mechanism constituted by rotatably mounting the other end of a lever (6) having a tip end hook (61) to a side face of the bottom plate (11) and lifting an intermediate portion of the lever by a spring (62) is provided, the tip end hook (61) is engaged with the lifting-up arm (51) in a state where the bottom plate (11) has been opened at 90° and the lifting-up arm (51) has fallen down without being lifted upward.

**Kindly add the following new claim:**

4. (New) A bottom opening type container according to claim 2, wherein a returning mechanism constituted by rotatably mounting the other end of a lever (6) having a tip end

hook (61) to a side face of the bottom plate (11) and lifting an intermediate portion of the lever by a spring (62) is provided, the tip end hook (61) is engaged with the lifting-up arm (51) in a state where the bottom plate (11) has been opened at 90° and the lifting-up arm (51) has fallen down without being lifted upward.

SECRET

-3-

**Remarks**

We respectfully request that the above-identified amendments entered into the file of the case. They are made to remove multiple dependent claims and to shorten the abstract to comply with new U. S. Patent Office rules and no new matter has been added.

An early action on the merits of the case is respectfully requested.

Respectfully submitted,



T. Daniel Christenbury  
Reg. No. 31,750

TDC:gj  
(215) 563-1810



**Marked up Version in the Abstract**

Please replace the abstract in its entirety with the clean copy which is attached.







by the self-weight of the container 1, the ascending and descending block 93 is floated up to open the cam pieces 94, so that the cam pieces 94 are rotated about the shafts 941 by the springs 96 to be opened. In this state, when the container 1 is lifted up, the ascending and descending block 93 moves along the guide groove 95 without being prevented by the cam pieces 94, and the bottom plates 11 are opened due to the weight of the content and the self-weights of the bottom plates 11 so that the content is discharged.

**[0006]** That is, when the container 1 is lifted up after it is lifted down up to a predetermined position and once landed, the bottom plates 11 open automatically to discharge the content.

**[0007]** In this manner, the container described in Japanese Patent Application Laid-Open No. 06-115869 publication can open the container bottom plates to discharge the content by only lifting-up and lifting-down operations conducted by a crane. However, in this container,

there is a problem a) that, since a clearance of a length h in a height direction is required in a bottom plate portion, the content may drop due to its nature;

a problem b) that, once the container is landed, the bottom plates are opened in any case, and the like.

**[0008]** An object of the present invention is to provide a bottom opening type container which solves such a problem, and where the bottom plates can be tightly closed without providing a clearance and where a selection about whether or not the bottom plates should be opened automatically can arbitrarily be made by a simple operation.

## SUMMARY OF THE INVENTION

**[0009]** (1) A bottom opening type container which is constituted with a side plate (13) and a pair of bottom plates (11), comprising: opening and closing shafts (12) of the bottom plates (11) which are mounted in the vicinity of a bottom portion of the side plate (13); engaging pins (14) which are provided in the vicinity of tip ends of the bottom plates (11); a pair of opening and closing arms (57) which are pivoted to opening and closing fulcrums (573) fixed to the side plate (13) and can retain the engaging pins (14) at lower end portions; intermediate links (56) whose one ends are coupled to upper and intermediate

[illegible]

**[0010]** (2) A bottom opening type container which is constituted with a side plate (13) and a pair of bottom plates (11), comprising: opening and closing shafts (12) of the bottom plates (11) which are mounted in the vicinity of a bottom portion of the side plate (13); engaging pins (14) which are provided in the vicinity of tip ends of the bottom plates (11); a pair of opening and closing arms (57) which are pivoted to opening and closing fulcrums (573) fixed to the side plate (13) and can retain the engaging pins (14) at lower end portions; intermediate links (56) whose one ends are coupled to upper and intermediate portions of the opening and closing arms (57); a block (55) which is connected to the other ends of the intermediate links (56); a lifting rod (52) which is screw-coupled to the block (55); a sleeve (53) which is inserted with the lifting rod (52); a rocker arm (54) which is mounted in the vicinity of a lower end of the sleeve (53) and which ascends and descends together with the sleeve (53); and a lifting-up arm (51) which is coupled to the lifting rod (52) via a pin (521), wherein the vicinities of both ends of the rocker arm (54) are engaged with upper end portions of the opening and closing arms (57), the lifting-up arm (51) has

two arms extending in different directions by 90° about the pin (521) serving as a rotation center, lifting holes (511), (512) are provided at respective holes, a pushing-down pin (513) is mounted near to the rotation center of one arm, and S-shaped slits (571) which are fitted to the rocker arm (54) in left and right directions at respective positions of opening and closing are provided in the opening and closing arms (57).

**[0011]** (3) A bottom opening type container according to claim 1 or 2, wherein a returning mechanism constituted by rotatably mounting the other end of a lever (6) having a tip end hook (61) to a side face of the bottom plate (11) and lifting an intermediate portion of the lever by a spring (62) is provided, the tip end hook (61) is engaged with the lifting-up arm (51) in a state where the bottom plate (11) has been opened at 90° and the lifting-up arm (51) has fallen down without being lifted upward.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0012]** Fig. 1 is a front view showing a state where bottom plates of a bottom opening type container of a first embodiment of the present invention has been closed;

**[0013]** Fig. 2 is a front view showing a state where the bottom plates of the bottom opening type container of the first embodiment of the present invention has been opened;

**[0014]** Fig. 3 is a partial front view showing an opening and closing control mechanism in the first embodiment of the invention;

**[0015]** Fig. 4 is a partial front view showing the opening and closing control mechanism in the first embodiment of the present invention;

**[0016]** Figs. 5 are partial front views showing a main portion of the opening and closing control mechanism in the first embodiment of the present invention;

**[0017]** Fig. 6 is a partial front view showing an opening and closing control mechanism in a second embodiment of the present invention;

**[0018]** Fig. 7 is a partial front view showing the opening and closing control mechanism in the second embodiment of the present invention;

**[0019]** Figs. 8 are front views showing an operation of a returning mechanism in a third embodiment of the present invention;

**[0020]** Fig. 9 is a front view of a bottom opening type container showing a conventional

[0021] Fig. 10 is a plan view of the bottom opening type container showing the prior art.

**[0022]** A bottom opening type container of the present invention is not lifted up directly when it is lifted up by a crane or the like, but it is configured such that a lifting-up rod for lifting up a container can be ascended and descended relative to a container side plate and bottom plate receiving links provided at a lower end portion of the lifting-up rod restrain engaging pins positioned at tip ends of a container bottom plates from the below, the engaging pins are released only when the lifting-up rod is lowered relative to the side plate by an opening and closing mechanism so that the bottom plates can be opened. Therefore, when a releasing operation is performed, the bottom plates are released by landing the container so that the content is discharged, and when the releasing operation is not performed, the cargo handling can be performed while the bottom plates are closed.

**[0023]** Alternatively, a portion to be lifted up by a crane is constituted by a lifting-up arm which has two arms and is rotatable by 90°, and the bottom plates are put in a closed state when the container is lifted up by one arm, while the bottom plates are put in a locked state when the container is lifted up by the other arm, so that opening and closing are controlled by changing the lifting-up state.

[First Embodiment]

**[0024]** A first embodiment of the present invention will be explained with reference to the drawings. Fig. 1 is a front view showing a state of a bottom opening type container 1 whose bottom plates have been closed, and Fig. 2 is a front view showing a state of the bottom opening type container whose bottom plates have been opened, where the same reference numerals are used to parts common to Figs. 9 and 10, and 5 denotes an opening and closing mechanism for the bottom plates 11, 51 denotes a lifting-up arm 51, 531 denotes a manual lever, 572 denotes engaging hook which opens and closes according to operation of the manual lever 531 and action of the opening and closing control mechanism 5 described later to retain the bottom plate 11, and 14 denotes an engaging pin provided at a tip end portion of the bottom plate 11 retained by the engaging hook 572.

[0025] As understood from Fig. 1, the bottom plates 11 of the container are approximately completely closed by engaging the engaging pins 14 with the engaging hooks 572, and it is unnecessary to provide such a clearance as viewed in Fig. 9 and described above.

[0026] Next, the opening and closing control mechanism 5 will be explained. Figs. 3 and 4 are front views which show the opening and closing control mechanism 5 in different states, respectively, according to the embodiment. The same reference numerals are used in parts common to the above-described embodiment. 51 denote a lifting-up arm which is engaged with a hook when the container is lifted up by a crane or the like, 52 denotes a lift rod which is coupled to the lifting-up arm 51 via a pin 521, 53 denotes a sleeve in which the lifting rod 52 is inserted, 54 denotes a rocker arm which is mounted in the vicinity of a lower end of the sleeve to ascend and descend together with the sleeve, 55 denotes a block which is fixed to the vicinity of the lower end of the lift rod 52 through a screw connection, 56 denotes an intermediate link whose one end is connected to the block 55, and 57 denotes an opening and closing arm which is connected to the other end of the intermediate link 56. A spring 532 is inserted between a lower end of the sleeve 53 and the block 55, and the manual lever 531 which is rotatable by 180° in a horizontal direction using the lifting rod 52 as a rotation shaft is inserted between an upper end of the sleeve 53 and the lifting arm 51. Further, an extension portion 522 of the lifting rod 52 is screwed into the block 55 from the below and it is inserted into a hole of a protrusion piece 13a in the vicinity of a container bottom portion so that the protrusion piece serves as a guide when the lifting rod 52 ascends and descends. The opening and closing arm 57 is rotatable about an opening and closing fulcrum 573 provided on the container bottom portion. In a state where the lower end engaging hook 572 is positioned vertically, as shown in Fig. 3, the hook engages the engaging pin 14 mounted to the bottom plate 11 of the bottom opening type container from the outside so that the hook maintains the bottom plate so as not to open. Further, an upper end portion of the opening and closing arm 57 is provided with a S-shaped slit 571 and it is engaged with a tip end portion of the above-described rocker arm 54 via a lock pin 541, and an upper and intermediate portion thereof is connected with the other end of the intermediate link 56, as described above.

[0027] The lifting arm 51 has one short arm and one L-shaped arm on both sides of a pin





**[0032]** Since the opening and closing control mechanism 5 of this embodiment has been configured in the above manner, one example of how to use the container will be explained as follows:

**[0033]** As shown in Fig. 3, the manual lever 531 is moved at the “Close” position on the left side, and even if the container is lifted up by using the lifting hole 511 to be moved or lifted down, the bottom plates do not open. The container is once landed and the manual lever 531 is rotated by 180° to be moved to the “Open” position on the right side, and when the container is lifted up and it is landed again, the bottom plates open so that the content is discharged. After the cargo is charged, when the empty container is landed again and the manual lever 531 is returned back to the close position, a cargo handling work can be performed with the container whose bottom plates have been closed, again.

**[0034]** In a case of this embodiment, when the manual lever 531 is moved to the “Close” position, the bottom plates of the container are prevented from opening, and all operations of lifting-up and lifting-down, a transverse movement, and opening and closing of the container can be performed by only operations in the crane, so that it is unnecessary to approach to a lifted cargo which is dangerous for a worker. In addition, since it can be confirmed clearly from a far position that the manual lever 531 is positioned at the “Close” position, all workers around the cargo can work safely.

[Second Embodiment]


**[0035]** A second embodiment of the present invention will be explained with reference to the drawings. Since a bottom opening type container itself is similar to that of the first embodiment, and there are many points common to the first embodiment regarding the opening and closing control mechanism, this embodiment will be explained mainly regarding different points below. Figs. 6 and 7 are front views showing an opening and closing control mechanism in different states, respectively, according to the embodiment. Same reference numerals will be used for parts common to parts which have been explained previously.

**[0036]** 51 denotes a lifting-up arm to which a hook is applied when the container is lifted up by a crane or the like. In this embodiment, the lifting-up arm 51 has two arms









## CLAIMS

1. A bottom opening type container which is constituted with a side plate (13) and a pair of bottom plates (11), comprising: opening and closing shafts (12) of the bottom plates (11) which are mounted in the vicinity of a bottom portion of the side plate (13); engaging pins (14) which are provided in the vicinity of tip ends of the bottom plates (11); a pair of opening and closing arms (57) which are pivoted to opening and closing fulcrums (573) fixed to the side plate (13) and can retain the engaging pins (14) at lower end portions; intermediate links (56) whose one ends are coupled to upper and intermediate portions of the opening and closing arms (57); a block (55) which is connected to the other ends of the intermediate links (56); a lifting rod (52) which is screw-coupled to the block (55); a sleeve (53) which is inserted with the lifting rod (52); a rocker arm (54) which is mounted in the vicinity of a lower end of the sleeve (53) and which ascends and descends together with the sleeve (53); a lifting-up arm (51) which is coupled to the lifting rod (52) via a pin (521); a manual lever (53) which is inserted between the lifting-up arm (51) and an upper end of the sleeve (53) to be rotatable by 180° in a horizontal direction using the lifting rod (52) as a rotation shaft; and a stopper for a lever (58) which is provided at a lower portion of the manual lever (53) to prevent the manual lever from lowering, wherein the vicinities of both ends of the rocker arm (54) are engaged with upper end portions of the opening and closing arms (57), the lifting-up arm (51) has one short arm and one L-shaped arm on both sides about the pin (521) serving as a rotation center, a pushing-down pin (513) is provided near to the rotation center of the short arm and a lifting hole (511) is provided at a tip end of the L-shaped arm, and S-shaped slits (571) which are fitted to the rocker arm (54) in left and right directions at respective positions of opening and closing are provided in the opening and closing arms (57).

2. A bottom opening type container which is constituted with a side plate (13) and a pair of bottom plates (11), comprising: opening and closing shafts (12) of the bottom plates (11) which are mounted in the vicinity of bottom portion of the side plate (13); engaging pins (14) which are provided in the vicinity of tip ends of the bottom plates (11); a pair of

opening and closing arms (57) which are pivoted to opening and closing fulcrums (573) fixed to the side plate (13) and can retain the engaging pins (14) at lower end portions; intermediate links (56) whose one ends are coupled to upper and intermediate portions of the opening and closing arms (57); a block (55) which is connected to the other ends of the intermediate links (56); a lifting rod (52) which is screw-coupled to the block (55); a sleeve (53) which is inserted with the lifting rod (52); a rocker arm (54) which is mounted in the vicinity of a lower end of the sleeve (53) and which ascends and descends together with the sleeve (53); and a lifting-up arm (51) which is coupled to the lifting rod (52) via a pin (521), wherein the vicinities of both ends of the rocker arm (54) are engaged with upper end portions of the opening and closing arms (57), the lifting-up arm (51) has two arms extending in different directions by 90° about the pin (521) serving as a rotation center, lifting holes (511), (512) are provided at respective holes, a pushing-down pin (513) is mounted near to the rotation center of one arm, and S-shaped slits (571) which are fitted to the rocker arm (54) in left and right directions at respective positions of opening and closing are provided in the opening and closing arms (57).

3. A bottom opening type container according to claim 1 or 2, wherein a returning mechanism constituted by rotatably mounting the other end of a lever (6) having a tip end hook (61) to a side face of the bottom plate (11) and lifting an intermediate portion of the lever by a spring (62) is provided, the tip end hook (61) is engaged with the lifting-up arm (51) in a state where the bottom plate (11) has been opened at 90° and the lifting-up arm (51) has fallen down without being lifted upward.

## ABSTRACT

In the present invention, such a structure is employed that a clearance in the vicinity of the bottom plates of a bottom opening type container is removed and one of automatic opening and closing of the container can arbitrarily be selected by a simple operation.

Specifically, a container is constituted with opening and closing shafts (12) of bottom plates (11) which are mounted in the vicinity of a bottom portion of a pair of side plates (13); engaging pins (14) which are provided in the vicinity of tip ends of the bottom plates (11); a pair of opening and closing arms (57) which are pivoted to opening and closing fulcrums (573) fixed to the side plate (13) and can retain the engaging pins (14) at lower end portions; intermediate links (56) whose one ends are coupled to upper and intermediate portions of the opening and closing arms (57); a block (55) which is connected to the other ends of the intermediate links (56); a lifting rod (52) which is screw-coupled to the block (55); a sleeve (53) which is inserted with the lifting rod (52); a rocker arm (54) which is mounted in the vicinity of a lower end of the sleeve (53) and which ascends and descends together with the sleeve (53); a lifting-up arm (51) which is coupled to the lifting rod (52) via a pin (521); a manual lever (53) which is inserted between the lifting-up arm (51) and an upper end of the sleeve (53) to be rotatable by 180° in a horizontal direction using the lifting rod (52) as a rotation shaft; and a stopper for a lever (58) which is provided at a lower portion of the manual lever (53) to prevent the manual lever from lowering, wherein the vicinities of both ends of the rocker arm (54) are engaged with upper end portions of the opening and closing arms (57), the lifting-up arm (51) has one short arm and one L-shaped arm on both sides about the pin (521) serving as a rotation center, a pushing-down pin (513) is provided near to the rotation center of the short arm and a lifting hole (511) is provided at a tip end of the L-shaped arm, and S-shaped slits (571) which are fitted to the rocker arm (54) in left and right directions at respective positions of opening and closing are provided in the opening and closing arms (57).

Fig. 1




Fig. 2






Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9





Fig. 10





**COMBINED DECLARATION, POWER OF ATTORNEY AND PETITION**  
(Page 2)

Attorney Docket No. 1066-02

I hereby claim foreign priority benefits under Title 35, United States Code, §119(a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT International Application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application(s) for patent or inventor's certificate or of any PCT International Application having a filing date before that of the application on which priority is claimed:

Number	Country	Date of Filing (day,month,year)	Priority Claimed
			<input type="checkbox"/> yes <input type="checkbox"/> no
			<input type="checkbox"/> yes <input type="checkbox"/> no
			<input type="checkbox"/> yes <input type="checkbox"/> no
			<input type="checkbox"/> yes <input type="checkbox"/> no
			<input type="checkbox"/> yes <input type="checkbox"/> no

I hereby claim the benefit under Title 35, United States Code, §119(e) or §120 (as applicable) of any United States application(s) or §365(c) of any PCT International Application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International Application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112:

\_\_\_\_\_  
(Application Serial No.)

\_\_\_\_\_  
(Filing Date)

\_\_\_\_\_  
(Status) (patented, pending, abandoned)

\_\_\_\_\_  
(Application Serial No.)

\_\_\_\_\_  
(Filing Date)

\_\_\_\_\_  
(Status) (patented, pending, abandoned)

**POWER OF ATTORNEY:** As a named inventor, I hereby appoint the registered attorneys listed under Customer No. 022469 and the following registered attorneys to prosecute this application and transact all business in the United States Patent and Trademark Office connected therewith:

T. Daniel Christenbury Reg. No. 31,750  
Guy T. Donatiello Reg. No. 33,167  
Paul A. Taufer Reg. No. 35,703  
Albert T. Keyack Reg. No. 32,906  
Jeffrey L. Eichen Reg. No. 41,496  
Austin R. Miller Reg. No. 16,602  
James A. Drobile Reg. No. 19,690  
Joan T. Kluger Reg. No. 38,940

Frank A. Cona Reg. No. 38,412  
Michael A. Patané Reg. No. 42,982  
Robert A. McKinley Reg. No. 43,793  
Stewart M. Wiener Reg. No. 46,201  
Stephenie W. Yeung Reg. No. 48,052

13

<b>SEND CORRESPONDENCE TO:</b> <u>IP Department</u> <u>Schnader Harrison Segal &amp; Lewis</u> <u>36th Floor, 1600 Market Street</u> <u>Philadelphia, PA 19103</u>	<b>DIRECT TELEPHONE CALLS TO</b> <b>ATTORNEY OF RECORD AT:</b>  (215) 563-1810
--	---

Attorney Docket No. 1066-02

☐ Original Application

☒ PCT National Application  
U.S. Designated Office

☐ Continuation or Divisional Application

☐ Continuation-in-Part Application

**COMBINED DECLARATION,  
POWER OF ATTORNEY AND PETITION**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled DROP-BOTTOM CONTAINER

☐ which is described in the specification and claims

☐ attached hereto.

☐ filed on \_\_\_\_\_

Application Serial No. \_\_\_\_\_

and was amended on \_\_\_\_\_

*(if applicable)*

■ which is described in International Application No. PCT/IP99/05369

filed September 30, 1999 and as amended on \_\_\_\_\_

\_\_\_\_\_, (if any),

which I have reviewed and for which I solicit a United States patent.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. §1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the national or PCT international filing date of the continuation-in-part application.

COMBINED DECLARATION, POWER OF ATTORNEY AND PETITION 123456789  
(Page 3)

Attorney Docket No. 1066-02

I hereby petition for grant of a United States Letters Patent on this invention.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

1. FULL NAME OF SOLE OR FIRST INVENTOR Ritsuo Nakajima		INVENTOR'S SIGNATURE <i>R. Nakajima</i>	DATE April 1, 2002
RESIDENCE Chiba, Japan		CITIZENSHIP Japanese	
POST OFFICE ADDRESS 10-22, Nishisakata 1-chome, Kimitsu-shi, Chiba 299-1145, Japan			
2. FULL NAME OF JOINT INVENTOR, IF ANY		INVENTOR'S SIGNATURE	DATE
RESIDENCE		CITIZENSHIP	
POST OFFICE ADDRESS			
3. FULL NAME OF ADDITIONAL JOINT INVENTOR, IF ANY		INVENTOR'S SIGNATURE	DATE
RESIDENCE		CITIZENSHIP	
POST OFFICE ADDRESS			
4. FULL NAME OF ADDITIONAL JOINT INVENTOR, IF ANY		INVENTOR'S SIGNATURE	DATE
RESIDENCE		CITIZENSHIP	
POST OFFICE ADDRESS			
5. FULL NAME OF ADDITIONAL JOINT INVENTOR, IF ANY		INVENTOR'S SIGNATURE	DATE
RESIDENCE		CITIZENSHIP	
POST OFFICE ADDRESS			
6. FULL NAME OF ADDITIONAL JOINT INVENTOR, IF ANY		INVENTOR'S SIGNATURE	DATE
RESIDENCE		CITIZENSHIP	
POST OFFICE ADDRESS			
7. FULL NAME OF ADDITIONAL JOINT INVENTOR, IF ANY		INVENTOR'S SIGNATURE	DATE
RESIDENCE		CITIZENSHIP	
POST OFFICE ADDRESS			